



SPECS

| FRAME | |
|------------------|--|
| SIZES | S,M,L,XL |
| COLORS | Electric Blue/Orange/White, Matt/Black/Neon Red/Charcoal, Yellow/Electric Blue/Black |
| FRAME | ALUXX-Grade Aluminum |
| FORK | SR Suntour XCT 26/27.5", 100mm Travel |
| COMPONENTS | |
| HANDLEBAR | Giant Sports Low , 31.8mm |
| STEM | Giant Sport Alloy, 10 Degree |
| SEATPOST | SP-219N Alloy, 30.9x350mm |
| SADDLE | Contact Comfort (Neutral) |
| PEDALS | One-Piece Black PP, 9/16" |
| DRIVETRAIN | |
| SHIFTERS | Shimano EF40 |
| FRONT DERAILLEUR | Shimano Tourney |
| REAR DERAILLEUR | Shimano Tourney |
| BRAKES | Tektro TKB172 |
| BRAKE LEVERS | Shimano EF41 |
| CASSETTE | Shimano HG-200, 12x32 |
| CHAIN | KMC Z51 |
| CRANKSET | ProWheel Flint, 42/32/24 |
| WHEELS | |
| BOTTOM BRACKET | Cartridge |
| RIMS | Giant GX28 27.5X32H / 26x32H |
| HUBS | Alloy, Sealed |
| SPOKES | Stainless 14G |
| TIRES | Giant Quickcross, 27.5x2.1/26x2.1 |

FEATURES

- ALUXX-grade butted aluminum frame
- SR Suntour XCT 100mm-travel fork
- Shimano 3x7-speed drivetrain with Tektro mechanical disc brakes
- Giant GX28 alloy double-wall rims with Giant Quickcross tires
- Color: Electric Blue/Orange/White, Matt/Black/Neon Red/Charcoal, Yellow/Electric Blue/Black



GEOMETRY

| FRAME | XXS (26") | XS (26") | S (26") | S (27.5") | M (27.5") | L (27.5") | XL (27.5") |
|--------------------------|-----------|----------|---------|-----------|-----------|-----------|------------|
| Seat Tube Length (mm) | 395 | 405 | 420 | 420 | 455 | 505 | 535 |
| Seat Tube Angle | 73.5° | 73.5° | 73.5° | 73.5° | 73.0° | 73.0° | 73.0° |
| Top Tube Length (mm) | 555 | 565 | 575 | 575 | 590 | 610 | 630 |
| Head Tube Length (mm) | 95 | 105 | 120 | 95 | 110 | 145 | 170 |
| Head Tube Angle | 68.0° | 68.0° | 68.0° | 68.0° | 68.0° | 68.0° | 68.0° |
| Fork Rake (mm) | 42 | 42 | 42 | 42 | 42 | 42 | 42 |
| Trail (mm) | 92 | 92 | 92 | 92 | 92 | 92 | 92 |
| Wheelbase (mm) | 1065 | 1076 | 1087 | 1080 | 1091 | 1114 | 1136 |
| Chain Stay Length (mm) | 420 | 420 | 420 | 435 | 435 | 435 | 435 |
| Bottom Bracket Drop (mm) | 35 | 35 | 35 | 50 | 50 | 50 | 50 |
| Stack (mm) | 556 | 565 | 579 | 581 | 595 | 628 | 651 |
| Reach (mm) | 390 | 398 | 403 | 403 | 408 | 418 | 431 |
| Stand Over Height (mm) | 702 | 710 | 723 | 721 | 747 | 789 | 814 |
| Handlebar Width (mm) | 620 | 660 | 660 | 660 | 660 | 700 | 700 |
| Stem Length (mm) | 50 | 50 | 70 | 70 | 70 | 90 | 90 |
| Crank Length (mm) | 160 | 165 | 170 | 170 | 170 | 175 | 175 |
| Wheel Size | 26" | 26" | 26" | 27.5" | 27.5" | 27.5" | 27.5" |

The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city / country.